

Envire Rubber Sheet & Tile

Manufacturer


Roppe Corporation
1602 N. Union Street
P.O. Box 1158
Fostoria, Ohio USA 44830-1158
Website - www.roppe.com
t: (419) 435.8546 tf: (800) 537.9527
f: (419) 435.1056
e-mail: sales@roppe.com

Product Description

Roppe Envire Rubber Sheet and Tile was developed for use in high traffic areas that require natural resilience, exceptional wear resistance and dimensional stability. Envire's quality rubber composition provides a quiet and extremely comfortable walking surface that has excellent resistance to abrasion, impact, scuffs, gouging, burns and most chemicals.

Features

PVC Free	Does Not Require A Finish
Phthalate Free	Resistant to Fungi
Noise-Reducing Material	Excellent Chemical Resistance
Superior Slip Resistance	Recyclable (IMPACT) Program
FloorScore® Certified	Qualifies for LEED® Credits



Envire Rubber Sheet & Tile

Sheet:

Nominal Dimensions: 74" x 50' x 2.5 mm
Nominal Area: 300 sq. ft.
Finish: Smooth
Weight Per Roll: ~ 260 lbs.
Quantity Per Pallet: 9 Rolls Per Pallet

Tile:

Nominal Dimensions: 24" x 24" x 2.5 mm
Finish: Smooth
Weight Per Tile: ~ 3 lbs.
Quantity Per Carton: 18 Tiles

Technical Data

LEED v2009 IEQ Credit 4.1: Qualifies
LEED v2009 IEQ Credit 4.3: Qualifies

ASTM F1344 - Rubber Floor Tile: Class I
ASTM E648 (NFPA 253) - Critical Radiant Flux: Class I, > 0.45 W/cm2
ASTM E662 (NFPA 258) - Smoke Density: Passes < 450
ASTM D412 - 10%Modulus: Excellent
ASTM D2240 - Durometer Hardness, Shore A: Passes
ASTM F970 - Static Load Limit: Passes, 250 PSI
ASTM F970 (Modified) - Max Weight: 1500 PSI
ASTM F925 - Chemical Resistance: Passes
ASTM D2047 - Slip Resistance: > 0.6
ASTM F1514 - Heat Stability: Passes
ASTM F1515 - Light Stability: Passes
ASTM D3389 - Abrasion Resistance: Passes
ASTM G21 - Resistance to Fungi: Excellent
ASTM E492/E989 - Impact Sound: IIC 50
ASTM E90 / E413 - Airborne Sound: STC 62
ASTM E2179 - Effectiveness of Floor: ΔIIC 11
Acclimation Time: 48 Hours
Storage & Acclimation Temperature: 65 ° - 85 ° F

Approved Adhesive* ([Visit our website for complete Adhesive recommendations](#))

SP-500 Aerosol Adhesive
AP-520 Acrylic Pressure Sensitive Adhesive
AW-510 Acrylic Wet-Set Adhesive
MS-700 Modified Silane Adhesive
EW-710 Epoxy Wet-Set Adhesive

Installation* ([Visit our website for complete Installation instructions](#))

All materials are to be delivered to the installation location within 48 hours of installation in its original packaging with labels intact. Store products in a dry area protected from the weather with temperatures maintained between 65° F (19°C) and 85° F (30°C). DO NOT stack pallets. Remove all plastic wrapping and strapping from the pallets and un-box all material in the installation area at least 48 hours prior to installation.

Maintenance* ([Visit our website for complete Maintenance instructions](#))

Refer to the Envire Maintenance information for detailed instructions on the Roppe Website.

Availability, Cost & Samples

Roppe Flooring products are sold through distribution. To locate the nearest distributor, visit www.roppe.com. or send an email to solutions@roppe.com

Technical Document Support

Additional product resources and technical documents are available online at www.roppe.com. For additional technical support, send an e-mail to solutions@roppe.com

Warranty

Roppe Provides a 5 year Limited Warranty for Envire rubber flooring. For additional information, see associated Warranty documents.

***For complete adhesive, installation & maintenance instructions, visit www.roppe.com**